

# i3LIGHTHOUSE PROJECTION MAT



## Maintenance and care instructions

### Ordinary care:

Regularly remove dirt using mild soap and warm water, rinse well with clean water, wipe dry with a clean cloth.

### Washing by hand or machine:

Use lukewarm water (max. 30°C) or set your machine to a programme for delicate cloths using neutral detergent. Do not wring or spin.

If necessary, iron underside only, using pressing cloth, maximum 110°C. Do not chlorine bleach. Do not tumble dry.

## Stain removal

For the removal of stains, it is necessary to:

- react immediately
- Clean the stain from edge to center, in order to avoid rings
- Only use non abrasive cleaners, cloths or brushes
- When using a cleaner or detergent, apply it to a clean cloth, not directly to the surface needing to be cleaned

### Water-soluble stains:

Fruit juice, coffee, tea, milk, wine, beer, coke:  
Immediately remove as much of the stain as possible, using a clean cloth or kitchen towel wash with lukewarm water with mild soap, rinse with clean water or diluted methylated spirit (10%)  
Blood, urine, egg:  
Use cold water, avoid warm water, rinse by dabbing with clean water

### Non water soluble stains:

#### Ballpoint ink

Immediately rinse with perchloroethylene or trichloroethylene

#### Chocolate, candy

Sponge with warm water (max. 40°C)

#### Chewing gum

Put ice cubes in a plastic bag and apply it to the gum. Wait a few minutes and gently remove the gum

## Care labeling

Color fastness to regular dry cleaning solvent used: perchloroethylene	EN UNI ISO 105 D01:2010	Grade 4-5
Color fastness to domestic commercial laundering	EN UNI ISO 105 C06:2010	Grade 4-5
Color fastness to dry pressing: Temperature 110°C	UNI EN ISO 105 X 11/98	Grade 5
Color fastness to damp pressing: Temperature 110°C	UNI EN ISO 105 X 11/98	Grade 4-5
Color fastness to wet pressing: Temperature 110°C	UNI EN ISO 105 X 11/98	Grade 4-5
Color fastness to abrasion (dry and wet) Crockmeter Mod. cm 1 Dry cotton	UNI EN ISO 105 X 12/2003	Grade 3
Wet cotton		

## Technical specifications



- **Composition:** PVC 88% - PES 8% - Cotton 4%
- **Weight:** 3130 grams
- **Width:** 170 x 110 cm
- **Thickness:** 3 mm

- **Color fastness to artificial light:** index 6  
\*scale from 1 to 8. 1 meaning very low color fastness

- **Fire safety:** complies with EN 2021

- **Abrasion resistance (Martindale):** 50.000 cycles  
\*Materials with an abrasion resistance above 40.000 cycles Martindale are suited for intensive use.

- **Chemical composition:** Phthalates free and complies with 2005/84/CE.\*

\*Directive 2005/84/CE is applicable to 'toys', meaning every product designed or destined to be played with by children younger than 14 years old. The safety of toys is harmonised on a European level in order to correspond to fundamental manufacturing requirements. The certifications of the European normalisation institutions are proof of the compliance with fundamental directives. Toys that qualify to these norms, receive the CE-mark of compliance.

